

Go Solo

BEST-IN-CLASS LIVE STREAMING
SOLUTION FOR ONLINE MEDIA



LIVEU SOLO

LiveU Solo is a professional-grade wireless video encoder offering one-touch streaming to Facebook Live and YouTube, as well as other popular social media networks and online channels. The light and compact Solo is perfectly suited for any type of mobile use allowing you to stream live video from anywhere.

SIMPLE – STREAM DIRECTLY TO LEADING SOCIAL NETWORKS

Just connect LiveU Solo to your camera, log into the web-based Solo portal to select your streaming destination and go live!

RELIABLE – GO LIVE FROM ANYWHERE

Solo combines up to four connections (2 cellular modems, Wi-Fi and LAN) and leverages a unique video transmission method - LRT™. This allows you to deliver rock-solid content in practically every scenario – on the move and in remote or crowded locations.

VERSATILE – ENRICH YOUR LIVE CONTENT

With Solo Studio, you have a variety of options to enhance your live feeds: this includes advanced graphics as well as simultaneous streaming to multiple online destinations. Solo can be connected to any professional camera with both SDI and HDMI options, allowing you to live stream video in full HD, going beyond smartphone quality.



LIVEU SOLO TECHNICAL SPECIFICATIONS

A/V ENCODING	Video: H.264 AVC high profile up to 5.5Mbps, Audio: AAC-LC
A/V ENCAPSULATION	LRT, RTMP
VIDEO INTERFACES	3G/HD/SD-SDI, HDMI 1.4, auto input detection
VIDEO RESOLUTIONS	1080p50/60/25/30/24, 1080i50/60, 720p50/60/25/30/24, PAL, NTSC full A/V auto detection
SIMULTANEOUS BONDING	In LRT mode bond up to 2x USB Modems, WiFi, and Ethernet. All valid connections provided are used while bonding
SUPPORTED TECHNOLOGIES	4G LTE, HSPA+, HSUPA, HSDPA, UMTS, CDMA EVDO Rev 0/A/B, Mobile WiMAX, and external Wi-Fi 802.11 a,b,g & n support
LOCAL & REMOTE CONTROL	Local control to start and stop the stream; screen displays video preview and bitrate status. Full unit control via the mobile friendly Solo Web Portal for functions including destination configuration
RESILIENCY & QUALITY	Optional LiveU Reliable Transport (LRT), featuring proprietary algorithms such as automatic Adaptive Bit Rate (ABR), automatic Forward Error Correction (FEC) and other lost packet recovery algorithms; video encoding bit rate is set automatically
INTERNAL BATTERY	Lithium Ion providing minimum of 2 hours of streaming
LATENCY	LRT mode latency ~5 seconds to allow for error correction
DATA INTERFACES	2x USB 2.0, 1x Ethernet
DIMENSIONS	95mm x 132mm x 43mm / 3.7" x 5.9" x 1.7" (W x H x D)
WEIGHT	518g (1lb) including Battery
TEMPERATURE	Operating: -5C to +45 (23F to 113F)



Go Solo

gosolo.tv

| www.facebook.com/LiveU.Fans

| www.twitter.com/liveu

